



LHS CABLE & RHS CABLE
ED0792



EZDown Instruction

NISSAN NP 300 2016 – ED0750

www.ezdown.co.za **GENERATION 2**

1

Metal Bars OFF
1st Right Hand Side

2

3

End fitting of cable side view

Swage

Cable

NB !! When fitting the cable make sure the swage on cable's end fitting is facing towards the metal body of vehicle

4

Use C - Cable stud to secure G drilling Jig while drilling pilot hole $\varnothing 5,0$

Drill hole A & B original hole

5

Increase hole sizes A & B $\varnothing 9,0$

Remove G and C

6

7

PUTTING IT INSIDE THE TAILGATE PANEL USING THE METAL HANDLE THEN BREAKING THE HANDLE OFF AFTER BY TWISTING THE METAL OFF

8

FROM OUTSIDE THE TAILGATE PANEL

9

FROM OUTSIDE THE TAILGATE PANEL

10

A

Right Hand Side

B

11

Fit LHS. LHS is determined when facing forward to the Load bin area.

Repeat on RHS from slide 1 to slide 3.

NB: When installed, please close tailgate gently to ensure that the cable is rotating properly and that there is no interference with any of the other hardware

NB: After installation please close tailgate gently to ensure that there is no interference with any hardware.

FITTING KIT CODE	MANUFACTURER	MODEL TYPE	YEAR	STOCKIST	PRODUCT	REVISION	LABOUR TIME	DATE	PAGE
ED0750	NISSAN	NP 300	2016 onwards	GENERAL USE	EZDOWN	4	20min	14/07/2017	1
TORQUE-N.m	★ 17N.m±2N.m		★ 17N.m±2N.m						

IMPORTANT: No liability will be incurred by Industrial Specialised Applications company, for injury, death, or property damage caused by a product which has been set up, operated, and/or installed contrary to EZDown installation guide/ manual, or which has been subjected to misuse, negligence, or accident, or which has been repaired or altered by anyone other than Industrial Specialised Applications, or which has been used in a manner or for a purpose for which the product was not designed.